

Optional Accessories

Wertheim offers a wide range of accessories. Different customer requirements can be taken into account.

Please note that the shown accessory variants depend on the safe model. Kindly check the respective model page.



VdS-approved Steel Plinth

For a comfortable use there is the possibility to put the safe on a VdS-approved steel plinth. The plinth height can be selected from 65 mm to 800 mm. Steel plinths are available for the following safe models: AL, AN, AWS, BG, BM, BWS and CM.



Fire Protection Door Rebate Seal

Safes that do not offer certified fire protection can be fitted with an optional fire protection door rebate seal.



Interior Lighting

The aluminium-look LED light with integrated motion detector is battery-operated and rechargeable. It is magnetic and can therefore be placed anywhere in the safe.

*representative image



IAS Switch Set for Alarm Systems

Models with IAS connection preparation can be ordered with a switch set. VdS-approved alarm detectors and distribution boxes (top side of safe door and inside of safe ceiling) enable correct monitoring of the door position and locking status. The switch set is installed by Wertheim, connection and fine adjustment have to be done on site.



NOTE: If a drawer/pull-out shelf is installed in the top position, a switch set is not possible for grade I, II and type CP safes. The connecting cable (door/carcass) is designed here as a hanging loop.



Additional Anchoring/Cable Holes

It is possible to prepare the safe (after technical inspection) with additional anchoring or cable holes, in addition to the standard holes, at customer-specified positions (side wall, rear wall, ceiling, floor).



NOTE: Take care of possible equipment/interior when choosing the position of additional holes - especially in the side wall. 1 piece of anchoring material is included as standard in the scope of delivery. If additional anchors are required, this must be mentioned when ordering.